

# Wisconsin

	VAPOR INTRUSION SCREENING LEVELS ( $\mu\text{g}/\text{m}^3$ ) <sup>1, 2, 3</sup>			
	Sub-Slab Residential	Sub-Slab Industrial/Commercial	Indoor Air Residential	Indoor Air Industrial/Commercial
<b>Benzene</b>	120	(530) <sup>4</sup> 1,600	3.6	(16) 16
<b>Tetrachloroethylene</b>	1,400	(6,000) 18,000	42	(180) 180
<b>Trichloroethylene</b>	70	(290) 880	2.1	(8.8) 8.8
<b>Vinyl Chloride</b>	57	(930) 2,800	1.7	(28) 28

Notes:

1. Wisconsin Department of Natural Resources vapor intrusion screening levels are noted in the table and can be found [here](#). The term “Vapor Intrusion Screening Levels” or “VISLs” is used as a generic term for regulatory standards.
2. The United States Environmental Protection Agency’s (US EPA) Vapor Intrusion Screening Levels (VISLs) link is included [here](#) for reference.
3. Site-specific evaluation or mitigation is required if the VISLs are exceeded. More information on vapor intrusion guidance can be found [here](#). Revised guidance was published in January 2018.
4. Levels in parenthesis are for “small commercial” areas. Values adjacent to levels in parenthesis are for “large commercial/industrial” areas.