

# Delaware

	VAPOR INTRUSION SCREENING LEVELS ( $\mu\text{g}/\text{m}^3$ ) <sup>1, 2, 3</sup>			
	Sub-Slab Residential	Sub-Slab Industrial/Commercial	Indoor Air Residential	Indoor Air Industrial/Commercial
<b>Benzene</b>	12	12	0.36	0.36
<b>Tetrachloroethylene</b>	140	140	4.2	4.2
<b>Trichloroethylene</b>	7	7	0.21	0.21
<b>Vinyl Chloride</b>	5.6	5.6	0.17	0.17

Notes:

1. The Delaware Department of Natural Resources and Environmental Control (DNREC) vapor intrusion screening levels are noted in the table and can be found here. The term “Vapor Intrusion Screening Levels” or “VISLs” is used as a generic term for regulatory standards.
2. Per the DNREC, the screening levels should be used for screening purposes only for the protection of human health and the environment. The screening levels are not to be construed as site-specific clean up levels. Site-specific evaluation or mitigation is required if the VISLs are exceeded. The DNREC document "[Vapor Intrusion Pathway Guidance](#)" provides further detail.
3. The United States Environmental Protection Agency’s (US EPA) Vapor Intrusion Screening Levels (VISLs) link is included [here](#) for reference.